

# Surface Mount Yellow Green Chip LED - 0603

**multicomp** PRO

**RoHS  
Compliant**



## Features

- 1.6mm × 0.8mm SMT LED, 0.7mm Thickness.
- Wide Viewing Angle.
- Ideal for Backlight and Indicator.
- Various Colorus and Lens Types Available.

## Applications

- Automotive: Backlighting in dashboard and switch.
- Telecommunication: Indicator and Backlighting in telephone and fax.
- Flat Backlight for LCD switch and symbol.

## Device Selection Guide

Part No.	Chip		Lens Colour
MP005928	Material	Emitted Colour	Water clear
	(InGaN)	Green	

## Absolute Maximum Ratings at TA=25°C

Parameter	Symbol	Value	Unit
Power Dissipation	P <sub>D</sub>	62	mW
Forward Current	I <sub>F</sub>	25	mA
Peak Forward Current*1	I <sub>FP</sub>	100	mA
Reverse Voltage	V <sub>R</sub>	5	V
Operating Temperature	T <sub>opr</sub>	-40°C To +85°C	
Storage Temperature	T <sub>stg</sub>	-40°C To +85°C	

Notes:

\*1: Pulse width≤0.1ms, Duty cycle≤1/10

## Electrical / Optical Characteristics at TA=25°C

Parameter	Symbol	Min.	Typ.	Max	Unit	Test Conditions
Forward Voltage	V <sub>F</sub>	1.8	—	2.6	V	I <sub>F</sub> =20mA
Reverse Current	I <sub>R</sub>	—	—	10	μA	V <sub>R</sub> =5V
Dominate Wavelength	λ <sub>D</sub>	566	—	576	nm	I <sub>F</sub> =20mA
Luminous Intensity	I <sub>V</sub>	48	—	100	mcd	I <sub>F</sub> =20mA
Viewing Angle	2θ <sub>1/2</sub>	—	120	—	Deg.	I <sub>F</sub> =20mA

Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or chromaticity), the typical accuracy of the sorting process is as follows:

1. wavelength: ±1nm
2. Luminous Intensity: ±15%
3. Forward Voltage: ±0.1V







Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
Element14.com/multicomp-pro

**multicomp** PRO

# Surface Mount Yellow Green Chip LED - 0603

**multicomp** PRO


## Typical Electrical/Optical Characteristics Curves



# Surface Mount Yellow Green Chip LED - 0603

**multicomp** PRO

## Diagram




### Notes:

1. All dimensions are in millimeters.
2. Tolerance is  $\pm 0.15$  unless otherwise noted.
3. Specifications are subject to change without notice.

## Soldering Profile


Reflow Soldering Profile For Lead-free SMT Process.



### Notes

1. We recommend the reflow temperature 245°C. ( $\pm 5^\circ\text{C}$ ) The maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to epoxy resin while it is exposed to high temperature.
3. Number of reflow process shall be 2 times or less.

## Recommended Soldering Pattern



## Part Number Table

Description	Part Number
SMD Chip LED, 0603, Yellow Green, 100mcd, 120°	MP005928

**Important Notice** : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro  
Farnell.com/multicomp-pro  
Element14.com/multicomp-pro

**multicomp** PRO

# Surface Mount Yellow Green Chip LED - 0603

multicomp<sup>PRO</sup>

## Tape Specifications

